

Seleção de Condensadores

Capacidade (KW)	T _{orvalho} 35 °C Água 25/30 °C				T _{orvalho} 40 °C Água 30/35 °C			T _{orvalho} 50 °C Água 40/45 °C			T _{orvalho} 60 °C Água 50/55 °C			Vazão de água M ³ /h
	Modelo				Modelo			Modelo			Modelo			
	BL14	BL26	BL50	BL95	BL26	BL50	BL95	BL26	BL50	BL95	BL26	BL50	BL95	
2,5	20	20			20			20			20			0,43
3,8	20	20			20			20			20			0,60
5,0	30	20			20			30			30			0,86
7,5	30	30			30			30			40			1,28
10,0	50	40			40			40			50			1,71
12,5		50	20		50	20		50	20		60	20		3,14
15,0		50	30		60	30		60	30		70	30		2,58
17,5		60	30		70	30		70	30			30		3,00
20,0		70	30			30			30			40		3,43
22,5			30			30			40			40		3,85
25,0			30			40			40			40		4,28
27,5			40			40			40			50		4,71
30,0			40			40			50			50		5,14
32,5			40			40			50			50		5,57
35,0			50			50			50			60		6,01
37,5			50			50			50			60		6,42
40,0			50			50			60			60	40	6,85
42,5			50			60			60			70	40	7,28
45,0			60			60			60	40		70	50	7,71
47,5			60	40		60	40		70	40			50	8,14
50,0			60	40		60	40			50			50	8,56
62,5				50			50			60			60	10,70
75,0				60			60			60			70	12,86
87,5				70			70			70			80	15,00
100,0				70			80			80			90	17,13
125,0				90			100			100			110	21,41
150,0				110			110			120			130	25,69
175,0				120			130			140			150	29,97
200,0				140			150			160				34,25